

(12) United States Patent

Schultheiss et al.

(10) Patent No.:

US 9,409,320 B2

(45) Date of Patent:

Aug. 9, 2016

(54) COLLAPSIBLE MANDREL FOR MANUFACTURING THREE-DIMENSIONAL **STRUCTURES**

(71) Applicant: GENERAL ELECTRIC COMPANY,

Schenectady, NY (US)

Inventors: David Schultheiss, Munich (DE); Swen

Zaremba, Munich (DE); Christoph

Ebel, Munich (DE)

Assignee: General Electric Company, Niskayuna,

NY (US)

Subject to any disclaimer, the term of this (*) Notice:

patent is extended or adjusted under 35

U.S.C. 154(b) by 691 days.

Appl. No.: 13/718,176

Dec. 18, 2012 (22)Filed:

Prior Publication Data (65)

US 2014/0167319 A1 Jun. 19, 2014

(51) Int. Cl.

B29C 33/44 (2006.01)B29C 33/48 (2006.01)B29C 33/54 (2006.01)

(52) U.S. Cl.

CPC B29C 33/448 (2013.01); B29C 33/485 (2013.01); **B29C** 33/54 (2013.01); B29K 2995/0012 (2013.01)

(58) Field of Classification Search

CPC B29C 33/448; B29C 33/485; B29C 33/54 See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

			Pastureau et al.
5,817,269	A *	10/1998	Younie B29C 33/38
			249/82
7,588,655	B2 *	9/2009	Pham B29C 43/12
			156/227
2009/0130442	A1*	5/2009	Christ C01B 31/0423
			428/367
2011/0304067	A1	12/2011	Rossfeldt et al.
2012/0228467	A1	9/2012	Wallen et al.

FOREIGN PATENT DOCUMENTS

S5868446 A * 4/1983 B22C 1/02 JP OTHER PUBLICATIONS

Kishi, et al; "Dismantlable Epoxy Adhesives for Recycling of Structural Materials," 16th International Conference on Composite Materials, ICCM-16—"A Giant Step Towards Environmental Awareness: From Green Composites to Aerospace:" Kyoto; Jul. 8, 2007 through Jul. 13, 2007.

Gardos, et al; "Solid Lubricated Turbine Bearings: Part I-Preparation of 316 degree C Lubricative Composites and Separators," ASLE Special Publication 1984, pp. 248-257, ASLE Proceedings-3rd International Conference on Solid Lubrication.

(Continued)

Primary Examiner — James Sanders (74) Attorney, Agent, or Firm — John P. Darling

ABSTRACT

A mandrel for manufacturing a three-dimensional structure from a composite material. The external surface of the mandrel can at least partially correspond to the inner surface of the three-dimensional structure. The mandrel can include a plurality of expandable particles configured to increase responsive to a threshold condition. The mandrel can be configured to crack responsive to a triggering condition.

20 Claims, 4 Drawing Sheets

